

As a temporary solution or a permanent installation, our IPP/ISP products are reliable, efficient tools for zonal isolation in critical oil, gas and geothermal applications. Built to the highest industry standards, Innovex IPP/ISP tools ensure an effective pressure seal and dependable operation.

Versatility is key to optimizing isolation. Tools in standard and customized configurations provide specific solutions – whatever the challenge.

The **Single-Set Inflatable Service Packer (ISP)** is used for isolating zones in open-hole or in casing. The tool is retrievable and may be used for testing, treating, production, or injection. The Single Set ISP may be used in vertical or deviated wells.

Features

- Robust mechanical tubing mandrel assembly
- Poppet valve or shear valve inflation control
- Inflatable elements available in 4 ft seal lengths
- Both cable reinforced and strip reinforced
- Custom sizes & materials available upon request

| ISP OD | | Inflation Valve | | Deflation Mechanism | |
|--------|-------|-----------------|-------|---------------------|------|
| inches | mm | Poppet | Shear | Rotate | Pull |
| 3.12 | 79.2 | Yes | | Yes | Yes |
| 3.62 | 91.9 | | Yes | Yes | Yes |
| 4.25 | 108.0 | Yes | Yes | Yes | Yes |
| 4.62 | 117.3 | Yes | Yes | Yes | Yes |
| 5.06 | 128.5 | Yes | Yes | Yes | Yes |
| 5.50 | 139.7 | Yes | Yes | Yes | Yes |
| 6.75 | 171.5 | Yes | Yes | Yes | Yes |
| 7.50 | 190.5 | Yes | Yes | Yes | Yes |
| 9.50 | 241.3 | Yes | Yes | Yes | Yes |

